Nomad

Experience pays off

With its comprehensive equipment and stylish, detailed solutions, the Nomad is the perfect caravan for demanding travellers. One highlight is the sophisticated Light Moments lighting concept, which is stylishly designed for the ultimate feel-good mood - regardless of the weather!

Technical info	
Overall length, approx.	691 - 942 cm
Overall width, approx.	230 - 250 cm
Overall height, approx.	265 cm
Headroom in living area, approx.	198 cm

Maximum values partly not possible for all models or only in connection with certain options.

Upholstery



+ Upholstery Ruby



+ Upholstery Champion O



+ Upholstery Chromo O

Plus factors

- + Something for everyone: a wide range of caravans with double and single-bed layouts
- Sophisticated exterior design: chic details such as a designer rear moulding with integrated lights, chrome trim on the side walls and chrome manoeuvring handles
- + Well-being atmosphere: exquisite, elegant living room design with atmospheric light concept
- + Cooking like at home: very well-equipped gourmet kitchen with illuminated kitchen back panel
- + Good as standard: ready to go thanks to comprehensive specifications





























+ Wood décor Noce Nagano

O optionally available











Nomad		460 EL	470 FR	490 BLF	490 EST	510 ER
Standard chassis		Lightweight chassis, 1500 kg	Lightweight chassis, 1500 kg	Lightweight chassis, 1500 kg	Lightweight chassis, 1500 kg	Lightweight chassis, 1500 kg
Overall length, approx.	cm	691	713	729	729	766
Body length approx.	cm	550	570	590	590	620
Overall width, approx.	cm	230	230	230	230	230
Overall height, approx.	cm	265	265	265	265	265
Circumferential dimension awning approx.	cm	948	968	988	988	1018
Headroom in living area, approx.	cm	198	198	198	198	198
Thickness floor / side walls / roof	mm	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34
Tire size		185 R14C 8PR	185 R14C 8PR	185 R14C 8PR	185 R14C 8PR	185 R14C 8PR
Bed dimension: Front bed, L x W, approx.	cm	200 x 85 / 190 x 85 / 190 x 210 O	200 x 135		200 x 85 / 190 x 85 / 190 x 210 O	200 x 85 / 190 x 85 / 190 x 210 O
Bed dimension: Central / middle bed, L X W, approx.	cm			185 x 105	185 x 90	
Bed dimension: Rear bed, L x W, approx.	cm	210 x 115	210 x 135	210 x 135		210 x 135
Sleeping berths standard / max.		3	4	3	3	4
Mass in running order (+/-5%)*	kg	1275 (1211 to 1339)*	1280 (1216 to 1344)*	1360 (1292 to 1428)*	1325 (1259 to 1391)*	1360 (1292 to 1428)*
$\label{eq:mass_period} \mbox{Manufacturer-specified mass for optional equipment}^*$	kg	140	123	51	86	38
Technically permissible maximum laden mass*	kg	1500	1500	1500	1500	1500
Heating		S 3004, 3.5 kW Gas / Combi 4 G/E, 4 kW Gas- Electric O	S 3004, 3.5 kW Gas / Combi 4 G/E, 4 kW Gas- Electric O	Combi 4 G/E, 4 kW Gas-Electric	Combi 4 G/E, 4 kW Gas-Electric	S 3004, 3.5 kW Gas / Combi 4 G/E, 4 kW Gas- Electric O
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	I	22	22	22	22	22
Fresh water tank capacity, total/ Fresh water tank capacity at driv filling	/ing I	43 / 15	43 / 15	48 / 15	48 / 15	43 / 15
Sockets: 12 V / 230 V / USB		0/6/1	0/8/1	0 / 7 / 1	0/6/1	0/9/1



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by











Nomad		510 LE	520 ELT	530 DR	560 FMK	560 RET
Standard chassis		Lightweight chassis, 1600 kg	Lightweight chassis, 1700 kg	Lightweight chassis, 1600 kg	Lightweight chassis, 1700 kg	Lightweight chassis, 1700 kg
Overall length, approx.	cm	762	762	788	818	818
Body length approx.	cm	630	630	650	675	675
Overall width, approx.	cm	230	250	230	250	250
Overall height, approx.	cm	265	265	265	265	265
Circumferential dimension awning approx.	cm	1028	1028	1048	1078	1078
Headroom in living area, approx.	cm	198	198	198	198	198
Thickness floor / side walls / roof	mm	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34
Tire size		185 R14C 8PR	195 R14C LI106	185 R14C 8PR	195 R14C LI106	195 R14C LI106
Bed dimension: Front bed, L x W, approx.	cm	210 x 135	200 x 85 / 190 x 85 / 190 x 210 O	205 x 150	200 x 155	230 x 150
Bed dimension: Central / middle bed, L X W, approx.	cm		185 x 90		230 x 115	2x 200 x 85 / 200 x 210 O
Bed dimension: Rear bed, L x W, approx.	cm	2x 200 x 85 / 200 x 215 O		210 x 135	195 x 70 / 190 x 75 / 195 x 75 O / 195 x 80 O / 195 x 70	
Sleeping berths standard / max.		4	3	4	5/60	4
Mass in running order (+/-5%)*	kg	1380 (1311 to 1449)*	1490 (1416 to 1565)*	1395 (1325 to 1465)*	1550 (1473 to 1628)*	1545 (1468 to 1622)*
Manufacturer-specified mass for optional equipment*	kg	117	117	100	33	48
Technically permissible maximum laden mass*	kg	1600	1700	1600	1700	1700
Heating		S 3004, 3.5 kW Gas / Combi 4 G/E, 4 kW Gas- Electric O	Combi 6 G/E, 6 kW Gas- Electric / Hot water heating, 6.4 kW Gas- Electric O	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas- Electric O / Hot water heating, 6.4 kW Gas-Electric	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas- Electric O / Hot water heating, 6.4 kW Gas-Electric O	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas- Electric O / Hot water heating, 6.4 kW Gas-Electric



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by











Nomad		510 LE	520 ELT	530 DR	560 FMK	560 RET
Refrigerator volume (thereof freezer), approx.	1	137 (15)	137 (15)	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	I	22	22	22	22	22
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	I	43 / 15	48 / 15	43 / 15	43 / 15	43 / 15
Sockets: 12 V / 230 V / USB		0/7/1	0/0/1	0/9/1	0/9/3	0/7/1



* INFO

The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by







Nomad		650 RQT	730 FKR	760 DR
Standard chassis		Lightweight chassis, 2000 kg	Lightweight chassis, 2200 kg	Lightweight chassis, 2200 kg
Overall length, approx.	cm	872	942	942
Body length approx.	cm	735	805	805
Overall width, approx.	cm	250	250	250
Overall height, approx.	cm	265	265	265
Circumferential dimension awning approx.	cm	1138	1208	1208
Headroom in living area, approx.	cm	198	198	198
Thickness floor / side walls / roof	mm	42 / 34 / 34	42 / 34 / 34	42 / 34 / 34
Tire size		185/70 R14 LI88	195/70 R14C LI104	195/70 R14C LI104
Bed dimension: Front bed, L x W, approx.	cm	230 x 155	200 x 155	200 x 150
Bed dimension: Central / middle bed, L X W, approx.	cm	200 x 155	200 x 75 / 2x 195 x 75 / 2x 195 x 75 O	
Bed dimension: Rear bed, L x W, approx.	cm		230 x 155	230 x 180
Sleeping berths standard / max.		4	7/80	4
Mass in running order (+/-5%)*	kg	1760 (1672 to 1848)*	1855 (1762 to 1948)*	1825 (1734 to 1916)*
Manufacturer-specified mass for optional equipment*	kg	127	195	255
Technically permissible maximum laden mass*	kg	2000	2200	2200
Heating		S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas- Electric O / Hot water heating, 6.4 kW Gas-Electric	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas- Electric O / Hot water heating, 6.4 kW Gas-Electric	S 5004, 6 kW Gas / Combi 6 G/E, 6 kW Gas- Electric O / Hot water heating, 6.4 kW Gas-Electric
Refrigerator volume (thereof freezer), approx.	1	137 (15)	86 (11) / 156 (29) O	156 (29) / 177 (35) O
Waste water tank, approx.	1	22	22	22



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by







Nomad	650 RQT	730 FKR	760 DR
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	43 / 15	43 / 15	43 / 15
Sockets: 12 V / 230 V / USB	0/9/1	0 / 10 / 3	0/9/1

O Optional equipment ─ Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication



The specified mass in running order is a standard value defined in the type approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5% of the mass in running order are legally permissible and possible. The permissible range in kilograms is stated in parentheses after the mass in running order. The mass for optional equipment specified by the manufacturer is an imputed value determined for each type and layout by which Dethleffs specifies the maximum weight available for factory-fitted optional equipment. The purpose of limiting optional equipment is to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of vehicles delivered by

Standard equipment	460 EL	470 FR	490 BLF	490 EST	510 ER	510 LE	520 ELT	530 DR	560 FMK	560 RET	650 RQT	730 FKR	760 DR
Chassis	-												
1.000													
Single axle premium wheel 195 R14 C L1106 (with steel wheel 1.700 kg and 1.800 kg) Tandem axle premium wheel 195/70 R14 C L1104 (with steel wheel 2.200 kg to 2.800 kg)												_	_
Tyres on steel wheels 185 R14 C 8 PR, up to and including 1.600 kg													
Tyres on steel wheels 185/70 R14 L188 up to and including 2.000 kg	_	_		_			_		_	_		_	_
Zinc-plated chassis with inertia braking system with reversing automatic							•		•	•	•	•	
Chassis features	Ė	Ď	Ť	Ě	Ě	Ť	Ť	Ť		Ě			
AAA self-adjusting brake													
ACS stabiliser													
High-quality brand-name tyres, designed for a speed of 100 km/h													
Lightweight corner steadies	•	•		•	•	•	•	•	•	•			•
Octagon shock absorber	•	•		•	•	•	•		•	•	•	•	•
Exterior features													
Floor of the gas bottle locker made of rot-resistant and robust corrugated aluminium													
Flyscreen door													
Front parts in gas locker area made of LFI (long fiber injection) technology, shock resistant, robust and repair-friendly	•	•	•	•	•	•	•	•	•	•	•	•	•
Fully-insulated wheel houses											•	•	
Midi Heki lift-and-tilt skylight incl. illuminated roof lining	•	•	•	•	•	•	•	•	•	•	•	•	•
One-piece habitation door with window											•	•	
Opening window in bathroom	_	_	_	•	_	_	_	_	•	•	•	•	•
Opening windows, trapezoid, insulated and double-glazed (graphite grey) with blackout and mosquito blinds	•	•	•	•	•	•	•	•	•	•	•	•	•
Panoramic front window ¹⁰⁾	_	_	•	_	_	_	_	_	_	_	_	_	_
Robust GRP roof													
Sidewall skirts with integrated side-marker lamps	•	•		•					•	•			
Skylight Mini Heki													
Space-saving gas locker door which opens upwards		•		•					•	•			
Spare wheel carrier in gas locker Storage space for 2 age bettles with 11 kg filling weight each													
Storage space for 2 gas bottles with 11 kg filling weight each													
Exterior design													
Front and rear in smooth sides white	•	•		•	•	•	•	•	•	•			•
Manoeuvring handles in chrome design													
Sides in hammer finish, white	Ť	Ť	_		_		Ť	Ť	Ť	_	İ	i	i
Access locker doors													
Access locker door front right side 997x419 mm		_	_	•	•	_	•	_	_	_	_	_	_
Access locker door rear left side 997x419 mm	_	_	•	_	_	_	_	_	_	•	_		_
Interior design													
Upholstery Ruby											•	•	
Wood décor Noce Nagano	•	•	•	•	•	•	•	•	•	•	•	•	•
Textile equipment													
7-zones double bed mattress, made of heat-regulating material	_	•	•	_	_	_	_	•		_	•	•	•
7-zones mattress left side, made of heat-regulating material		_	_					_	_		_	_	_
7-zones mattress right side, made of heat-regulating material	•	_	_	•	•	•	•	_	_	•	_	_	_
Furniture layouts													
AirPlus - perfect air circulation in the interior and rear ventilation of the overhead lockers and sideboards	•	•	•	•	•	•	•	•	•	•	•	•	•
Bunk bed with 2 sleeping berths, foldable	_	_	_	_	_	_	_	_		_	_	_	_
Bunk bed with 2 sleeping berths, not foldable	_	_	-	_	_	_	_	_	_	_	_	•	_
Bunk beds with safety net and ladder	_	_	-	_	_	_	_	_		_	_	•	_
One-legged telescopic table, height adjustable	-	•	•	_	•	_	•	•	•	•	•	•	•

Standard equipment	П	FR	BLF	EST	ER	E	ELT	DR	560 FMK	RET	RQT	FKR	DR
	460 EL	470 FR	490 BLF	490 EST	510 ER	510 LE	520 ELT	530 DR	560	560 RET	650 RQT	730 FKR	760 DR
Seating lounge converts to bed	•		•	•		•				•		•	•
Special slatted frame with flexible natural rubber holders, opening for optimal use of storage compartments under the beds	•	•	•	•	•	•	•	•	•	•	•	•	•
Kitchen													
Generous drawers with soft closing for absolutely silent closing	•	•	•	•	•	•	•	•	•	•	•	•	•
Kitchen worktop with indirect lighting	•				•						•		
Large fridge with 137 liters capacity and 15 liters freezer compartment	•	•	•	•	•	•	•	•	•		•	_	_
Practical 3-flames cooker with electric ignition	•												
Practical apothecary drawers (depending on layout)	•	•	•	•	•	•	•	•	•	•	•	•	•
Spacious fridge with 86-litre volume and 11 litre freezer	_	-	-	-	_	_	_	_	_	-	_	•	_
Bathroom													
Integrated design washbasin made of solid surface material	•	•	•	•	•	•	•	•	•	•	•	•	•
Shower tray	•	•	•	•	•	•	•	•	•	•	•	•	•
Skylight with mosquito net	•							•				•	
Heating													
Gas heating S 3004 with automatic ignition	•	•	_	_	•	•	_	_	_	_	_	-	_
Gas heating S 5004 with automatic ignition	_	_	_	_	_	_	_	•	•	•	•	•	•
Hot air system	•											•	
Electrical installation													
12 V power supply throughout vehicle	•	•	•	•	•	•	•	•	•	•	•	•	•
Awning light 12V	•	•	•	•	•	•	•	•	•	•	•	•	•
CEE external output socket for 230V on-board electrics													
Compact power distribution unit with 230V safety device and 12V fuse box in wardrobe incl. powerful 340W transformer	•	•	•	•	•	•	•	•	•	•	•	•	•
Illuminated kitchen back panel	•												•
Indirect lighting													
LED light bar system 12V (on head-side of bed and in seating lounge)	•											•	
USB port for spotlight bar	•	•	•	•	•	•	•	•	•	•	•	•	•
Water supply													
Electric water supply	•	•	•	•	•	•	•	•	•	•	•	•	•
Fresh water tank 38 l	•											•	
Hot water supply	•	•	_	_		•	_	•	•	•	•	•	
Mobile 22 l waste water tank	•						•	•				•	

Packages Nomad

Package	Styling Package white (single axle) (13254)	Styling Package white (single axle) (13254)	Styling Package white (single axle) (13254)	Styling Package white (tandem axle) (13256)	Styling Package white (tandem axle) (13256)	Styling Package white (tandem axle 2.8 t) (13258)
Smooth sides white	Х					
17" alloy wheels in Dethleffs design (single axle)	Х	Х	х			
Draw bar cover	Х	Х	х	х	Х	x
Large support feet, 4 pc.	Х	Х	Х	Х	Х	x
Solid rubber support wheel with support load indicator	Х	Х	Х	Х	Х	x
Manoeuvring handles in chrome design	Х	Х	х	х	Х	x
Rear light carrier with high attachment and roof rails	Х	Х	х	х	Х	x
Front moulding with high attachment and roof rails	Х	Х	х	х	Х	x
Smooth sides white		Х				
Smooth sides white			х	х		
17" alloy wheels in Dethleffs design (tandem axle)				х	Х	
Smooth sides white					Х	x
Tyres on alloy wheels 195/70 R14 C LI104, 2200 kg to 2800 kg						х
Additional weight (kg)*	45.7	48.3	51.1	41.1	43.4	47.4



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Package	Styling Package silver (single axle) (13255)	Styling Package silver (single axle) (13255)	Styling Package silver (single axle) (13255)	Styling Package silver (tandem axle) (13257)	Styling Package silver (tandem axle) (13257)	Styling Package silver (tandem axle 2.8 t) (13259)
Smooth sides titanium silver metallic	Х					
17" alloy wheels in Dethleffs design (single axle)	Х	х	Х			
Draw bar cover	Х	Х	Х	Х	х	x
Large support feet, 4 pc.	Х	х	х	х	х	x
Solid rubber support wheel with support load indicator	Х	х	х	x	х	x
Manoeuvring handles in chrome design	Х	х	X	X	X	x
Rear light carrier with high attachment and roof rails	Х	х	х	x	х	x
Front moulding with high attachment and roof rails	Х	х	х	x	х	x
Smooth sides titanium silver metallic		X				
Smooth sides titanium silver metallic			X	X		
17" alloy wheels in Dethleffs design (tandem axle)				x	х	
Smooth sides titanium silver metallic					х	x
Tyres on alloy wheels 195/70 R14 C LI104, 2200 kg to 2800 kg						Х
Additional weight (kg)*	45.7	48.3	51.1	41.1	43.4	47.4

Package	Winter Comfort Package Combi 4 (10479)	Winter Comfort Package Combi 4 (10479)	Winter Comfort Package Combi 6 (9536)	Winter Comfort Package Combi 6 (9536)	Winter Comfort Package Combi 6 (9536)	Winter Comfort Package for Combi heating (10481)
Electric floor heating	Х	Х	Х	Х	Х	Х
Waste water pipes insulated and heated	Х	Х	x	Х	x	х
Insulated threader hose	Х	Х	х	Х	x	х
XPS insulation for front, rear and sides (depending on vehicle size)	Х					
Hot air heating Combi 4 G/E incl. digital control unit	Х	Х				
XPS insulation for front, rear and sides (depending on vehicle size)		Х	х			х
Hot air heating Combi 6 G/E incl. digital control unit			x	Х	x	
XPS insulation for front, rear and sides (depending on vehicle size)				Х		
XPS insulation for front, rear and sides (depending on vehicle size)					х	
Additional weight (kg)*	47.6	50.1	50.1	52.8	55	35.1



Package	Winter Comfort Package SNOW (5459)	Winter Comfort Package SNOW (5459)	Winter Comfort Package SNOW (5459)	Winter Comfort Package SNOW PLUS (5551)	Winter Comfort Package SNOW PLUS (5551)	Winter Comfort Package SNOW PLUS (5551)
Hot water heating	Х	Х	Х	Х	Х	х
Electric floor heating	Х	Х	Х			
Waste water pipes insulated and heated	Х	Х	Х	Х	Х	х
XPS insulation for front, rear and sides (depending on vehicle size)	Х			Х		
XPS insulation for front, rear and sides (depending on vehicle size)		Х			Х	
XPS insulation for front, rear and sides (depending on vehicle size)			Х			х
Hot water floor heating (only in comb. with option 205)				Х	Х	Х
Additional weight (kg)*	74.1	76.8	79	75.1	77.8	80

Package	Mover Autonomy Package (single axle) (5560)	Mover Autonomy Package (tandem axle) (5561)
Mover manoeuvring support for single-axle	X	
Electric Autonomy equipment	X	X
Mover manoeuvring support for tandem-axle		Х
Additional weight (kg)*	70	98

Package	Water and Electric Autonomy Package Combi 4 (11031)	Water and Electric Autonomy Package Combi 6 (11032)	Water & Electric Autonomy Package with Combi or hot water heating system (9943)
Hot air heating Combi 4 G/E incl. digital control unit	Х		
Electric Autonomy equipment	Х	Х	x
Fresh water tank 70 l	Х	Х	x
Hot air heating Combi 6 G/E incl. digital control unit		Х	
Additional weight (kg)*	55.5	55.5	40.5

Safety Package (8950)

ATC Trailer Control

DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater

Smoke detector

Additional weight (kg)*

Shower Package (6105)

Shower equipment with shower fittings and curtain

City water connection

Additional weight (kg)*

 \triangle Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	470 FR	490 BLF	490 EST	510 ER	510 LE	520 ELT	530 DR	560 FMK	560 RET	650 RQT	730 FKR	760 DR
Chassis																
17" alloy wheels in Dethleffs design (single axle)	STP	10	11608	0	0	0	0	0	0	0	0	0	0	-	_	_
17" alloy wheels in Dethleffs design (tandem axle) Tyres on alloy wheels 185 R14 C LI102, up to and including	STP	0	11609											0	0	0
1600 kg	_	0	836	0	0	0	0	0	0	_	0	_	_	_	_	_
Tyres on alloy wheels 185/70 R14 L188, up to and including 2000 kg	_	0	840	_	-	-	-	_	-	-	_	-	_	0	-	_
Tyres on alloy wheels 195 R14 C LI106, 1700 kg and 1800 kg	_	2	838	0	0	0	0	0	0	0	0	0	0	_	_	_
Tyres on alloy wheels 195/70 R14 C LI104, 2200 kg to 2800 kg	STP	4	859	-	-	-	-	-	-	-	-	-	-	0	0	0
Weight upgrade																
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	24	278	0	0	0	0	0	-	-	0	_	-	-	-	_
Weight upgrade 1.700 kg (incl. steel wheel 195 R14 C LI106)	_	0.3	278	_	_	_	_	_	0	_	_	_	_	_	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	31.6	279	_	_	_	_	_	_	0	_	_	_	_	_	-
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	27	279	_	0	0	0	0	_	_	0	0	0	_	_	_
Weight upgrade 1.800 kg (incl. steel wheel 195 R14 C LI106)	_	8	279	_	_	_	_	_	0	_	_	_	_	_	_	_
Weight upgrade 1.900 kg (incl. alloy wheel 225/70 R15 C LI112)	-	27	394	_	_	_	_	_	_	0	0	0	0	_	_	_
Weight upgrade 2.000 kg (incl. alloy wheel 225/70 R15 C L1112)	_	27	138	_	_	_	_	_	_	0	0	0	0	_	_	_
Weight upgrade 2.200 kg (incl. steel wheel 195/70 R14 C LI104)	_	1.5	6351	_	_	_	_	_	_	_	_	_	_	0	_	_
Weight upgrade 2.500 kg (incl. steel wheel 195/70 R14 C LI104)	_	1.5	496	_	_	_	-	_	-	-	_	-	_	0	_	-
Weight upgrade 2.500 kg (incl. steel wheel 195/70 R14 C L1104)	_	0	496	_	_	_	_	_	_	_	_	_	_	_	0	0
Weight upgrade to 1.600 kg	_	24	322	0	0	0	0	0	_	_	_	_	_	_	_	_
Weigth upgrade 2.800 kg (incl. steel wheel 195/70 R14 C LI104)		24.9	7713	_	_	_	_	_	_	_	_	_	_	_	0	0
Chassis features																
ATC Trailer Control	SHP	4	748	0	0	0	0	0	0	0	0	0	0	0	0	0
Breakdown kit	_	1	620	0	0	0	0	0	0	0	0	0	0	0	0	0
Draw bar cover	STP	2	434	0	0	0	0	0	0	0	0	0	0	0	0	0
Large support feet, 4 pc.	STP	1	6348	0		0		0	0	0	0	0	0	0	0	0
Solid rubber support wheel with support load indicator Spare tyre with alloy wheel 185 R14 C LI 102, up to and	STP	2	10063	0	0	0	0	0	0	0	0	0	0	0	0	0
including 1.600 kg	_	17	837	0	0	_	0	0	0	_	0	_	_	_	_	_
Spare tyre with alloy wheel 185/70 R14 LI 88, up to and including 2.000 kg	_	18	841	_	_	_	_	_	_	_	_	_	_	0	_	_
Spare tyre with alloy wheel 195 R14 C 8PR-LI 106, 1.700 kg and 1.800 kg	_	19	839	0	0	-	0	0	0	0	0	0	_	_	-	_
Spare tyre with alloy wheel 195/70 R14 C-LI 102, 2.200 kg to 2.800 kg	_	19	861	_	_	_	_	_	_	_	_	_	_	0	0	0
Spare tyre with alloy wheel 225/70 R15 C LI 112 , 1.900 kg and 2.000 kg $$	_	23.5	1092	_	-	-	-	-	-	0	-	0	-	-	-	_
Spare tyre with steel wheel 185 R14 C 8 PR, up to and including 1.600 kg	_	18	831	0	0	-	0	0	0	-	0	-	-	-	-	_



Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	470 FR	490 BLF	490 EST	510 ER	510 LE	520 ELT	530 DR	560 FMK	560 RET	650 RQT	730 FKR	760 DR
Spare tyre with steel wheel 185/70 R14 LI 88, up to and including 2.000 kg	_	18	835	_	_	_	_	-	-	-	_	-	-	0	_	_
Spare tyre with steel wheel 195 R14 C LI 106, 1.700 kg and 1.800 kg	_	19.5	833	0	0	_	0	0	0	0	0	0	_	_	_	_
Spare tyre with steel wheel 195/70 R14 C-LI 104, 2.200 kg to 2.800 kg	_	20	860	_	_	_	-	-	-	-	-	-	-	0	0	0
Wheel trims for 14" tyres	_	2	276	0	0	0	0	0	0	0	0	0	0	0	0	0
Exterior features																
Cassette awning 3750x2500 mm, manual	_	25.5	6928	0	0	_	-	_	-	_	-	_	_	_	_	_
Cassette awning 4000x2500 mm, manual	_	27.5	6928	_	_	0	0	0	0	0	_	_	_	_	_	_
Cassette awning 4500x2500 mm, manual	_	30	6928	_	_	_	_	_	_	_	0	0	0	_	_	_
Cassette awning 5500x3000 mm, manual	_	50.6	6928	_	_	_	_	_	_	_	_	_	_	0	_	_
Cassette awning 6000x3000 mm, manual		54.6	6928	_	_	_	_	_	_	_	Ξ	_	_	_	0	0
Flush-fitting windows (not possible for front and rear windows) ⁸⁾	_	3	7561	0	0	0	0	0	0	0	0	0	0	0	0	0
Front window	_	4	982	0	_	_	0	0	•	0	0	_	•	•	_	0
Front window (bed area), if washroom in front	_	5	855	_	0	_	_	_	_	_	_	0	-	_	0	_
Heki II skylight incl. illuminated roof lining	_	8	274	0	0	_	0	0	0	0	0	0	0	0	0	0
Rear window	_	4	1108		_	0	_	_	0	_		_	_	_		
XPS insulation for front, rear and sides (depending on vehicle size)	WI-KO	17.6	179	0	0	_	_	_	-	_	_	_	_	_	_	_
XPS insulation for front, rear and sides (depending on vehicle size)	WI-KO	20.1	179	_	_	0	0	0	0	0	0	_	_	0	_	_
XPS insulation for front, rear and sides (depending on vehicle size)	WI-KO	22.8	179	_	_	_	_	_	-	-	_	0	0	-	_	-
XPS insulation for front, rear and sides (depending on vehicle size)	WI-KO	25	179	_	_	_	-	_	_	-	_	_	_	_	0	0
Exterior design																
Front moulding with high attachment and roof rails	STP	1	627	0	0	0	0	0	0	0	0	0	0	0	0	0
Rear light carrier with high attachment and roof rails	STP	11	624	0	0	0	0	0	0	0	0	0	0	0	0	0
Smooth sides titanium silver metallic	STP	18.7	659	0	0	_	_	_	_	_	_	_	_	_	_	_
Smooth sides titanium silver metallic	STP	21.3	659	_	_	0	0	0	0	0	0	_	_	_	_	_
Smooth sides titanium silver metallic	STP	24.1	659	_	_	_	_	_	_	_	_	0	0	0	_	_
Smooth sides titanium silver metallic	STP	26.4	659	_	_	_	_	_	_	_	_	_	_	_	0	0
Smooth sides white	STP	18.7	443	0	0	_	_	_	_	_	_	_	-	_	-	_
Smooth sides white	STP	21.3	443	_	_	0	0	0	0	0	0	_	_	_	_	_
Smooth sides white	STP	24.1	443	_	_	_	_	_	_	_	_	0	0	0	_	_
Smooth sides white	STP	26.4	443	_	_	_	_	_	_	_	_	_	_	_	0	0
Access locker doors																
Access locker door front left 997x419 mm	_	2.2	1079	_		_	_	0	_	0	_	•	_	_	•	_
Access locker door front left side 1069x299 mm	_	2	1083	_	_	_	_	_	0	_	_	_	_	_	_	_
Access locker door front left side 648x348 mm	_	2	1071	Ξ	0	_	_	0	_	0	0	_	_	_	_	0
Access locker door front right side 1069x299 mm	-	2	1084		_	_	_	_	0	_	_	_	0	0	_	_
Access locker door front right side 648x348 mm	_	2	1072	Ξ	_	_	_	_	_	_	•	_	_	_	_	0
Access locker door rear left side 1069x299 mm	_	2	1085	_	_	_	_	_	_	_	_	_	_	_	0	_
Access locker door rear left side 749x297 mm	_	2	1077	0	0	_	_	_	_	_	_	_	_	_	_	_



Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	470 FR	490 BLF	490 EST	510 ER	510 LE	520 ELT	530 DR	560 FMK	560 RET	650 RQT	730 FKR	760 DR
Access locker door rear right side 1069x299 mm	_	2	1086	_	_	_	_	0	_	_	0	_	_	_	0	
Access locker door rear right side 749x297 mm	_	2	1078	0	0	_	_	_	_	_	_	_	_	_	_	_
Access locker door rear right side997x419 mm	_	2.2	1082	_	_	_	_	_		_	_	_	0	•	_	_
Interior design																
Upholstery Champion	_	0	10489	0	0	0	0	0	0	0	0	0	0	0	0	0
Upholstery Chromo	_	0	10488	0	0	0	0	0	0	0	0	0	0	0	0	0
Textile equipment																
7-zones double bed mattress, made of heat-regulating material with watergel cover	_	4	8214	_	0	0	-	-	-	-	0	0	-	0	0	0
7-zones mattress left side, made of heat-regulating material with watergel cover	-	2	8215	0	_	-	0	0	0	0	_	_	0	_	_	_
7-zones mattress right side, made of heat-regulating material with watergel cover	_	5	8216	0	_	_	0	0	0	0	_	_	0	-	_	_
Corner head rests for U-shaped seating lounge	_	2	9236	_	0	_	_	0	_	_	0	0	0	0	0	0
Loose carpet		8.5	513	0	0	0	0	0	0	0	0	0	0	0	0	0
Furniture layouts																
Bunk bed with 2 sleeping berths, not foldable, instead of seating lounge	_	0	9775	_	_	_	_	_	_	_	_	_	_	_	0	_
Bunk bed with 3 sleeping berths, not foldable	_	20	200	_	_	_	_	_	_	_	_	0	_	_	_	_
Single beds convert to double bed	_	5	685	0	_	_	0	0	0	0	_	_	0	_	_	_
Slatted bed frame with adjustable head section	_	1	871	0	_	_	0	0	0	0	_	_	0	_	_	_
Interior features																
2 kg fire extinguisher	_	3.5	843	0	0	0	0	0	0	0		0	0	0	0	0
Smoke detector	SHP	0.5	8949	0	0	0	0	0	0	0	0	0	0	0	0	0
Kitchen																
Extractor fan		3	785	0	0	_	0	0	0	0	0	0	0	0	0	0
Kitchen unit with large fridge (175 l), separate freezer and electric ignition	-	18	429	_	-	-	-	-	-	-	-	-	-	-	0	•
Kitchen worktop extension, foldable	_	1	1107	_	0	_	_	0	_	_	_	_	0	0	0	0
Large fridge with 177 l volume and 35 l freezer, with oven (TecTower)	_	15	936	_	-	-	-	-	-	-	-	-	_	-	-	0
Oven		17	572	0	0	0	0	0	0	0	0	0	0	0	0	_
Bathroom																
Bathroom in alternative design		4	604	_	_	_	_	_	_	_	_	0	_	_	0	_
Multimedia																
FS-SAT system Voyager 65 Digimatic		10	1049	_	0	0	0	0	0	0	_	_	0	0	0	0
Flat screen TV 22" incl. DVD player and receiver	_	3.5	1103	0	0	0	0	0	0	0	0	0	0	0	0	0
Multifunctional external connection, 12 V, 220 V, TV and SAT	_	1	611	0	0	0	0	0	0	0	0	0	0	0	0	0
Preparation for flat screen TV (antenna cable and TV bracket)	_	2	678	0	0	0	0	0	0	0	0	0	0	0	0	0
SAT parabol antenna flat 65 Easy 65 Twin	_	14	879		0	0	0	0	0	0		0	0	0	0	0
TV preparation in sleeping area	_	2	9360											0		
Heating																
Electric floor heating	WI-KO	9	387	0	0	0	0	0	0	0	0	0	0	0	0	0
Fan 12 V with automatic speed control for S 5004	_	2	178	_	_	_	_	_	_	_	0	0	0	0	0	0



Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	470 FR	490 BLF	490 EST	510 ER	510 LE	520 ELT	530 DR	560 FMK	560 RET	650 RQT	730 FKR	760 DR
Fan 12V for S 3004	_	2	177	0	0	_	_	0	0	_	_	_	_	_	_	_
Hot air heating Combi 4 G/E incl. digital control unit	WEA-P, WI-KO	15	10480	0	0	•	•	0	0	-	_	_	-	_	_	_
Hot air heating Combi 6 G/E incl. digital control unit	WEA-P, WI-KO	15	9427	_	_	_	-	_	-	•	0	0	0	0	0	0
Hot water floor heating (only in comb. with option 205) 9)	WI-KO	10	674	_	_	_	_	_	_	0	0	0	0	0	0	0
Hot water heating	WI-KO	40	205	_	_	_	-	_	_	0	0	0	0	0	0	0
Ultraheat additional heating for S 3004, electric 220 V	_	2	364	0	0	_	_	0	0	_	_	_	_	_	_	_
Ultraheat additional heating for S 5004, electric 220 V	_	2	422	_	_	_	_	_	_	_	0	0	0	0	0	0
Air Conditioning																
Pre-wiring for A/C	_	0	172	0	0	0	0	0	0	0	0	0	0	0	0	0
Roof A/C	_	35	8145	0	0	0	0	0	0	0	0	0	0	0	0	0
Electrical installation						İ										
Electric Autonomy equipment	WEA-P, M-P	38	492	0	0	0	0	0	0	0	0	0	0	0	0	0
Water supply																
City water connection	DUP	2	414	0	0	0	0	0	0	0	0	0	0	0	0	0
Exterior shower	_	2	396	0	0	0	0	0	0	0	0	0	0	0	0	0
Fresh water tank 70 l	WEA-P	2.5	592	0	0	0	0	0	0	0	0	0	0	0	0	0
Shower equipment with shower fittings and curtain	DUP	5	1097	0	0	0	0	0	0	0	0	0	0	0	0	0
Waste water pipes insulated and heated	WI-KO	5	520	0	0	0	0	0	0	0	0	0	0	0	0	0
Gas supply																
DuoControl safety gas pressure regulator with crash sensor and EisEx gas regulator heater	SHP	2.5	784	0	0	0	0	0	0	0	0	0	0	0	0	0
Gas socket (exterior)	_	1	187	0	0	0	0	0	0	0	0	0	0	0	0	0
Packages																
Mover Autonomy Package (single axle)	_	70	5560	0	0	0	0	0	0	0	0	0	0	_	_	_
Mover Autonomy Package (tandem axle)	_	98	5561	_	_	_	_	_	_	_	_	_	_	0	0	0
Safety Package	_	7	8950	0	0	0	0	0	0	0	0	0	0	0	0	0
Shower Package	_	7	6105	0	0	0	0	0	0	0	0	0	0	0	0	0
Styling Package silver (single axle)	_	51.1	13255	_	_	_	_	_	_	_	_	0	0	_	-	_
Styling Package silver (single axle)	_	48.3	13255	_	_	0	0	0	0	0	0	_	_	Ξ	_	_
Styling Package silver (single axle)	_	45.7	13255	0	0	_	_	_	_	_	_	_	_	_	_	_
Styling Package silver (tandem axle 2.8 t)	_	47.4	13259	_	_	_	_	_	_	_	Ξ	_	_	_	0	0
Styling Package silver (tandem axle)	_	43.4	13257	_	_	_	_	_	_	_	_	_	_	_	0	0
Styling Package silver (tandem axle)	_	41.1	13257	_	_	_	_	_	_	_	Ξ	_	_	0	_	_
Styling Package white (single axle)	_	45.7	13254	0	0	_	_	_	_	_	_	_	_	_	-	_
Styling Package white (single axle)	_	48.3	13254		_	0	0	0	0	0	0	_	_	_	_	_
Styling Package white (single axle)	_	51.1	13254	_	_	_			_	_	_	0	0	_	_	
Styling Package white (tandem axle 2.8 t)	_	47.4	13258	Ξ	_	_	_	_	_	_	Ξ	_	_	_	0	0
Styling Package white (tandem axle)	_	43.4	13256	_	_	-				_	-			_	0	0
Styling Package white (tandem axle)	_	41.1	13256	Ξ	_	_	_	Ξ	_	_	Ξ	_	_	0	_	_
Water & Electric Autonomy Package with Combi or hot water heating system	-	40.5	9943	_	_	0	0	_	-	0	_	-	-	_	_	_
Water and Electric Autonomy Package Combi 4	_	55.5	11031	0	0	_	_	0	0	-	_	_	_	_	_	_



Optional equipment*	Included in package	Additional weight (kg)*	Code	460 EL	470 FR	490 BLF	490 EST	510 ER	510 LE	520 ELT	530 DR	560 FMK	560 RET	650 RQT	730 FKR	760 DR
Water and Electric Autonomy Package Combi 6	_	55.5	11032	_	_	_	_	_	_	_	0	0	0	0	0	0
Winter Comfort Package Combi 4	_	50.1	10479	_	_	_	_	0	0	_	_	_	_	_	_	_
Winter Comfort Package Combi 4	_	47.6	10479	0	0	_	_	_	_	_	_	_	_	_	_	_
Winter Comfort Package Combi 6	_	50.1	9536	_	_	_	_	_	_	_	0	_	_	0	_	_
Winter Comfort Package Combi 6	_	55	9536	_	_	_	_	_	_	_	_	_	_	_	0	0
Winter Comfort Package Combi 6	_	52.8	9536	_	_	_	_	_	_	_	_	0	0	_	_	_
Winter Comfort Package SNOW	_	76.8	5459	_	_	_	_	_	_	_	_	0	0	_	_	_
Winter Comfort Package SNOW	_	74.1	5459	_	_	_	_	_	_	0	0	_	_	0	_	_
Winter Comfort Package SNOW	_	79	5459	_	_	_	_	_	_	_	_	_	_	_	0	0
Winter Comfort Package SNOW PLUS	_	80	5551	_	_	_	_	_	_	_	_	_	_	_	0	0
Winter Comfort Package SNOW PLUS	_	77.8	5551	_	_	_	_	_	_	_	_	0	0	_	_	_
Winter Comfort Package SNOW PLUS	_	75.1	5551	_	_	_	_	_	_	0	0	_	_	0	_	_
Winter Comfort Package for Combi heating	_	35.1	10481	_	_	0	0	_	_	0	_	_	_	_	_	_
Miscellaneous																
Registration documents (CoC papers)	_	0	15151	•	•	*	*	•	+	*	*	•	+	•	*	•

O Optional equipment ─ Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication

STP Styling Package SHP Safety Package WI-KO Winter Comfort Package WEA-P Water and Electric Autonomy Package M-P Mover Package DUP Shower Package



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the payload. The specified additional weight for packages and optional equipment shows the additional weight compared with the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the mass for optional equipment specified by the manufacturer in the model overviews. This is an imputed

IMPORTANT INFORMATION REGARDING THE SELECTION OF YOUR CARAVAN

When purchasing a caravan, it is especially important to select not only an appealing design, but also the right layout. Weight also plays an essential role here. Family, friends, optional equipment, accessories, and baggage – there should be enough space for all of this. At the same time, there are legal and technical limits for configuration and loading. Each caravan is designed for a certain weight which must not be exceeded during travel. This raises a question for caravan buyers: How should I configure my vehicle to accommodate baggage and accessories according to my needs without causing the vehicle to exceed this maximum weight? To help you make this decision, we have provided you some information below that is particularly important when selecting your vehicle from our product range:

1. The technically permissible maximum laden mass...

... is a value specified by the manufacturer which the vehicle must not exceed. Based on the layout, Dethleffs specifies an upper limit for the vehicle, which can vary from layout to layout (e.g. 1,600 kg, 1,700 kg). You will find the corresponding specification for each layout in the technical data.









	Caravans		460 EL	470 ER	470 FR	500 QSK
	Sleeping berths standard / max.		3	3	4	5/6 🔾
	Technically permissible maximum laden mass*	kg	1500	1500	1500	1500
	Manufacturer-specified mass for optional equipment*	kg	180	188	158	96
)	Mass in running order (± 5 %)*	kg	1235 (1173 to 1297)*	1225 (1164 to 1286)*	1245 (1183 to 1307)*	1295 (1130 to 1360)*

2. The mass in running order...

: - - - - - - - - - - - - - - - -

... consists – to put it simply – of the basic vehicle with standard equipment. It is legally permissible and possible for the mass in running order of your vehicle to deviate from the nominal value specified in the sales documents. The permissible tolerance is \pm 5%. The permissible range in kilograms is stated in parentheses after the mass in running order. In order to provide you with full transparency regarding possible weight deviations, Dethleffs weighs each vehicle at the end of the line and informs your trading partner of the weighing result of your vehicle for forwarding to you. For detailed explanations of the mass in running order and the effect of tolerances on the minimum payload and the payload , please refer to the "Legal notes" section.

3. The standard sleeping berths...

... are specified by the manufacturer and shown in the sales documents. The number of sleeping berths can be increased (e.g. 3-person bunk bed) or, if required, reduced (e.g. sideboard instead of seating group) by selecting optional equipment.









Caravans		460 EL	470 ER	470 FR	500 QSK
Sleeping berths standard / max.		3	3	4	5/6 🔾
Technically permissible maximum laden mass*	kg	1500	1500	1500	1500
Manufacturer-specified mass for optional equipment*	kg	180	188	158	96
Mass in running order ((\pm 5 %) *	kg	1235 (1173 to 1297)*	1225 (1164 to 1286)*	1245 (1183 to 1307)*	1295 (1130 to 1360)*

4. The mass for optional equipment specified by the manufacturer...

... is a value set for each layout by Dethleffs for the maximum mass of optional equipment that can be ordered. This limit is intended to ensure that the minimum payload, i.e. the legally required free mass for baggage and retrofitted accessories, is actually available for the load capacity of the vehicles delivered by Dethleffs. If, in exceptional cases, the weighing at the end of the line nevertheless shows that the actual load capacity falls short of the minimum payload due to a permissible weight deviation, we will check together with your trading partner and you whether we should, for example, increase the load capacity of the vehicle or remove optional equipment before delivering the vehicle. For detailed explanations of the effects of the tolerances on the minimum payload and the payload, please refer to the "Legal notes" section.

Optional equipment*	Included in package	Price	Additional weight (kg)*	Code	460 EL	470 ER	470 FR
Bathroom							
Bathroom in alternative design	-	399,-	4	604	-	-	-
Multimedia							
Multifunctional external connection, 12 V, 220 V, TV and SAT	-	1.129,-	10	1049	-	0	0
Flat screen TV 22" incl. DVD player and receiver	-	999,-	3.5	1103	0	0	0
Flac Scient 17 22 mei. 070 player and receiver		,,,,	5.5	1103			

5. The additional weight of optional equipment and packages...

... increases the actual mass of the vehicle (= mass in running order plus selected optional equipment) and reduces the payload. The specified value shows the additional weight compared to the standard equipment of the respective layout. The total weight of the selected packages and optional equipment must not exceed the mass for optional equipment specified by the manufacturer.